



HVL 400

Halogen-Metaldampf Lampe

Metal halide lamp

Lámpara halógena de vapor de mercurio

| | | | | |
|-------------------|-------------------|---------------------------------|-------------|---------------|
| Lampentyp | Lamp type | Tipo de lámpara | HVL 400 | ASTRALUX |
| Artikel-Nr. | Part-No. | No.-Parte | A345-401870 | Ordering code |
| Leistung | Power | Potencia | 400 | W |
| Spannung | Arc voltage | Tensión | 135 | V |
| Strom | Current | Corriente | 3,65 | A |
| Lichtstrom | Luminous flux | Flujo luminoso | 33000 | lm |
| Lichtausbeute | Luminous efficacy | Eficiencia luminosa | 82,5 | lm/W |
| Farbtemperatur | Colour temperatur | Temperatura de color | 4000 | °K (CCT) |
| Optisches Zentrum | Light center | Centro óptico | 175+-5 | mm (LCL) |
| Farbwiedergabe | Color rendering | Nivel de reproducción cromática | 65 | Ra (CRI) |
| | | | 2B | DIN 5035 |
| Lebensdauer | Rated life | Duración/vida útil | 10000 | Hrs. |
| Glaskörper | Bulb | Ampolla/bulbo | tubular | |
| Typ | Type | Tipo | hard | |
| Ausführung | Finish | Acabo | clear | |
| Sockel | Cap/base | Casquillo/base | E40 | |
| Abmessungen | Dimension | Dimensiones | diameter 46 | mm ØD |
| | | | length 275 | mm L (MOL) |
| | | | weight 200 | g |
| | | | universal | |
| | | | 38 | µF/50Hz |
| | | | required | |
| | | | required | |
| | | | 49 | Quantity |
| | | | | ANSI |
| | | | 61167 | IEC |
| | | | 73/23/EEC | CE-EC |
| | | | 61167 | DIN EN |
| | | | 131613 | VDE Reg.-Nr. |
| | | | 45013-KRQ | ISO 9001 |
| Brennstellung | Burning position | Posición de funcionamiento | | |
| Kondensator | Capacitor | Condensador | | |
| Vorschaltgerät | Control gear | Balasto | | |
| Zündgerät | Ignitor | Ignitor | | |
| Stück/VE | Piece/box | Piezas/caja | | |
| ANSI-Nr. | ANSI-No. | No.-ANSI | | |
| IEC Norm | IEC Norm | IEC Norma | | |
| EG Konformität | EG Conformity | CE Conformidad | | |
| VDE Zertifikat | VDE Certificat | VDE Certificado | | |
| Qualitäts System | Quality system | Sistema de calidad | | |
| Anmerkungen | Remarks | Notas | | |

Information in our Catalogue, Data sheet and Price list are subject to technical and formal changes without prior notice. Operating values and dimensions are valid with the usual slight deviations