



MVLI 160

Mischlichtlampe

Blended light lamp

Lámpara de luz mixta

Lampentyp	Lamp type	Tipo de lámpara	MVLI 160	ASTRALUX
Artikel-Nr.	Part-No.	No.-Parte	A220-162457	Ordering code
Leistung	Power	Potencia	160	W
Spannung	Arc voltage	Tensión	240	V
Strom	Current	Corriente	0,75	A
Lichtstrom	Luminous flux	Flujo luminoso	3000	lm
Lichtausbeute	Luminous efficacy	Eficiencia luminosa	18,75	lm/W
Farbtemperatur	Colour temperatur	Temperatura de color	3400	°K (CCT)
Optisches Zentrum	Light center	Centro óptico	na	mm (LCL)
Farbwiedergabe	Color rendering	Nivel de reproducción cromática	63	Ra (CRI)
			2B	DIN 5035
Lebensdauer	Rated life	Duración/vida útil	6000	Hrs.
Glaskörper	Bulb	Ampolla/bulbo	elliptical	
Typ	Type	Tipo	E1/2, soft/hard	
Ausführung	Finish	Acabo	phosphor coated	
Sockel	Cap/base	Casquillo/base	E27	mm ØD
Abmessungen	Dimension	Dimensiones	diameter 76	mm L (MOL)
			length 177	g
			weight 95	
			universal	
Brennstellung	Burning position	Posición de funcionamiento	na	µF/50Hz
Kondensator	Capacitor	Condensador	not required	
Vorschaltgerät	Control gear	Balasto	not required	
Zündgerät	Ignitor	Ignitor	not required	
Stück/VE	Piece/box	Piezas/caja	12	Quantity
ANSI-Nr.	ANSI-No.	No.-ANSI		ANSI
IEC Norm	IEC Norm	IEC Norma		IEC
EG Konformität	EG Conformity	CE Conformidad	73/23/EEC	CE-EC
			SF19/98	DIN EN
VDE Zertifikat	VDE Certificat	VDE Certificado		VDE Reg.-Nr.
Qualitäts System	Quality system	Sistema de calidad	45013-KRQ	ISO 9001
Anmerkungen	Remarks	Notas		

Information in our Catalogue, Data sheet and Price list are subject to technical and formal changes without prior notice. Operating values and dimensions are valid with the usual slight deviations