



## MVLI 250

### Mischlichtlampe

### Blended light lamp

### Lámpara de luz mixta

Lampentyp	Lamp type	Tipo de lámpara	MVLI 250	ASTRALUX
Artikel-Nr.	Part-No.	No.-Parte	A220-252864	Ordering code
Leistung	Power	Potencia	250	W
Spannung	Arc voltage	Tensión	230/240	V
Strom	Current	Corriente	1,15	A
Lichtstrom	Luminous flux	Flujo luminoso	5600	lm
Lichtausbeute	Luminous efficacy	Eficiencia luminosa	22,5	lm/W
Farbtemperatur	Colour temperatur	Temperatura de color	3400	°K (CCT)
Optisches Zentrum	Light center	Centro óptico	na	mm (LCL)
Farbwiedergabe	Color rendering	Nivel de reproducción cromática	62	Ra (CRI)
			2B	DIN 5035
Lebensdauer	Rated life	Duración/vida útil	6000	Hrs.
Glaskörper	Bulb	Ampolla/bulbo	elliptical	
Typ	Type	Tipo	2, hard	
Ausführung	Finish	Acabo	phosphor coated	
Sockel	Cap/base	Casquillo/base	E40	mm ØD
Abmessungen	Dimension	Dimensiones	diameter 91	mm L (MOL)
			length 227	g
			weight 150	
			universal	µF/50Hz
Brennstellung	Burning position	Posición de funcionamiento	na	
Kondensator	Capacitor	Condensador	not required	Quantity
Vorschaltgerät	Control gear	Balasto	not required	ANSI
Zündgerät	Ignitor	Ignitor	not required	IEC
Stück/VE	Piece/box	Piezas/caja	12	CE-EC
ANSI-Nr.	ANSI-No.	No.-ANSI	73/23/EEC	DIN EN
IEC Norm	IEC Norm	IEC Norma	SF19/98	VDE Reg.-Nr.
EG Konformität	EG Conformity	CE Conformidad	45013-KRQ	ISO 9001
VDE Zertifikat	VDE Certificat	VDE Certificado		
Qualitäts System	Quality system	Sistema de calidad		
Anmerkungen	Remarks	Notas		

Information in our Catalogue, Data sheet and Price list are subject to technical and formal changes without prior notice. Operating values and dimensions are valid with the usual slight deviations