



MVLI 250 A

Mischlichtlampe

Blended light lamp

Lámpara de luz mixta

Lampentyp	Lamp type	Tipo de lámpara	MVLI 250 A	ASTRALUX
Artikel-Nr.	Part-No.	No.-Parte	A220-255762	Ordering code
Leistung	Power	Potencia	250	W
Spannung	Arc voltage	Tensión	220/230	V
Strom	Current	Corriente	1,15	A
Lichtstrom	Luminous flux	Flujo luminoso	5800	lm
Lichtausbeute	Luminous efficacy	Eficiencia luminosa	23	lm/W
Farbtemperatur	Colour temperatur	Temperatura de color	3400	°K (CCT)
Optisches Zentrum	Light center	Centro óptico	na	mm (LCL)
Farbwiedergabe	Color rendering	Nivel de reproducción cromática	60	Ra (CRI)
			2B	DIN 5035
Lebensdauer	Rated life	Duración/vida útil	6000	Hrs.
Glaskörper	Bulb	Ampolla/bulbo	elliptical	
Typ	Type	Tipo	2, hard	
Ausführung	Finish	Acabo	phosphor coated	
Sockel	Cap/base	Casquillo/base	E39, Mogul	
Abmessungen	Dimension	Dimensiones	diameter 90	mm ØD
			length 227	mm L (MOL)
			weight 160	g
			universal	
Brennstellung	Burning position	Posición de funcionamiento	na	µF/50Hz
Kondensator	Capacitor	Condensador	not required	
Vorschaltgerät	Control gear	Balasto	not required	
Zündgerät	Ignitor	Ignitor	12	Quantity
Stück/VE	Piece/box	Piezas/caja		ANSI
ANSI-Nr.	ANSI-No.	No.-ANSI		IEC
IEC Norm	IEC Norm	IEC Norma	73/23/EEC	CE-EC
EG Konformität	EG Conformity	CE Conformidad	SF19/98	DIN EN
VDE Zertifikat	VDE Certificat	VDE Certificado	45013-KRQ	VDE Reg.-Nr.
Qualitäts System	Quality system	Sistema de calidad		ISO 9001
Anmerkungen	Remarks	Notas		

Information in our Catalogue, Data sheet and Price list are subject to technical and formal changes without prior notice. Operating values and dimensions are valid with the usual slight deviations