



SVLE 350 Exchange

Natriumdampf-Hochdrucklampe

High pressure sodium vapor lamp

Lámpara de vapor de sodio en alta presión

Lampentyp	Lamp type	Tipo de lámpara	SVLE 350 EX	ASTRALUX
Artikel-Nr.	Part-No.	No.-Parte	A143-402870	Ordering code
Leistung	Power	Potencia	350	W
Spannung	Arc voltage	Tensión	117	V
Strom	Current	Corriente	3,45	A
Lichtstrom	Luminous flux	Flujo luminoso	35000	lm
Lichtausbeute	Luminous efficacy	Eficiencia luminosa	100	lm/W
Farbtemperatur	Colour temperatur	Temperatura de color	2100	°K (CCT)
Optisches Zentrum	Light center	Centro óptico	na	mm (LCL)
Farbwiedergabe	Color rendering	Nivel de reproducción cromática	20	Ra (CRI)
			4	DIN 5035
Lebensdauer	Rated life	Duración/vida útil	14000	Hrs.
Glaskörper	Bulb	Ampolla/bulbo	elliptical	
Typ	Type	Tipo	2, hard	
Ausführung	Finish	Acabo	coated	
Sockel	Cap/base	Casquillo/base	E40	
Abmessungen	Dimension	Dimensiones	diameter 122	mm ØD
			length 292	mm L (MOL)
			weight 260	g
Brennstellung	Burning position	Posición de funcionamiento	universal	
Kondensator	Capacitor	Condensador	25	µF/50Hz
Vorschaltgerät	Control gear	Balasto	required	
Zündgerät	Ignitor	Ignitor	not required	
Stück/VE	Piece/box	Piezas/caja	12	Quantity
ANSI-Nr.	ANSI-No.	No.-ANSI	na	ANSI
IEC Norm	IEC Norm	IEC Norma	60662	IEC
EG Konformität	EG Conformity	CE Conformidad	73/23/EEC	CE-EC
			60662	DIN EN
VDE Zertifikat	VDE Certificat	VDE Certificado	132008	VDE Reg.-Nr.
Qualitäts System	Quality system	Sistema de calidad	45013-KRQ	ISO 9001
Anmerkungen	Remarks	Notas	Exchange	

Information in our Catalogue, Data sheet and Price list are subject to technical and formal changes without prior notice. Operating values and dimensions are valid with the usual slight deviations