



SVLE 50 Standard

Natriumdampf-Hochdrucklampe

High pressure sodium vapor lamp

Lámpara de vapor de sodio en alta presión

Lampentyp	Lamp type	Tipo de lámpara	SVLE 50	ASTRALUX
Artikel-Nr.	Part-No.	No.-Parte	A140-052430	Ordering code
Leistung	Power	Potencia	50	W
Spannung	Arc voltage	Tensión	85	V
Strom	Current	Corriente	0,76	A
Lichtstrom	Luminous flux	Flujo luminoso	3300	lm
Lichtausbeute	Luminous efficacy	Eficiencia luminosa	66	lm/W
Farbtemperatur	Colour temperatur	Temperatura de color	2100	°K (CCT)
Optisches Zentrum	Light center	Centro óptico	na	mm (LCL)
Farbwiedergabe	Color rendering	Nivel de reproducción cromática	20	Ra (CRI)
			4	DIN 5035
Lebensdauer	Rated life	Duración/vida útil	24000	Hrs.
Glaskörper	Bulb	Ampolla/bulbo	elliptical	
Typ	Type	Tipo	1, soft	
Ausführung	Finish	Acabo	coated	
Sockel	Cap/base	Casquillo/base	E27	
Abmessungen	Dimension	Dimensiones	diameter 72	mm ØD
			length 163	mm L (MOL)
			weight 60	g
			universal	
			10	µF/50Hz
			required	
			required	
			20	Quantity
			na	ANSI
			60662	IEC
			73/23/EEC	CE-EC
			60662	DIN EN
			132008	VDE Reg.-Nr.
			45013-KRQ	ISO 9001
Brennstellung	Burning position	Posición de funcionamiento		
Kondensator	Capacitor	Condensador		
Vorschaltgerät	Control gear	Balasto		
Zündgerät	Ignitor	Ignitor		
Stück/VE	Piece/box	Piezas/caja		
ANSI-Nr.	ANSI-No.	No.-ANSI		
IEC Norm	IEC Norm	IEC Norma		
EG Konformität	EG Conformity	CE Conformidad		
VDE Zertifikat	VDE Certificat	VDE Certificado		
Qualitäts System	Quality system	Sistema de calidad		
Anmerkungen	Remarks	Notas		

Information in our Catalogue, Data sheet and Price list are subject to technical and formal changes without prior notice. Operating values and dimensions are valid with the usual slight deviations