



SVLE 50 Internal Ignitor

Natriumdampf-Hochdrucklampe

High pressure sodium vapor lamp

Lámpara de vapor de sodio en alta presión

Lampentyp	Lamp type	Tipo de lámpara	SVLE 50 I	ASTRALUX
Artikel-Nr.	Part-No.	No.-Parte	A143-052430	Ordering code
Leistung	Power	Potencia	50	W
Spannung	Arc voltage	Tensión	85	V
Strom	Current	Corriente	0,76	A
Lichtstrom	Luminous flux	Flujo luminoso	3300	lm
Lichtausbeute	Luminous efficacy	Eficiencia luminosa	66	lm/W
Farbtemperatur	Colour temperatur	Temperatura de color	2100	°K (CCT)
Optisches Zentrum	Light center	Centro óptico	na	mm (LCL)
Farbwiedergabe	Color rendering	Nivel de reproducción cromática	20	Ra (CRI)
			4	DIN 5035
Lebensdauer	Rated life	Duración/vida útil	12000	Hrs.
Glaskörper	Bulb	Ampolla/bulbo	elliptical	
Typ	Type	Tipo	1, soft	
Ausführung	Finish	Acabo	coated	
Sockel	Cap/base	Casquillo/base	E27	
Abmessungen	Dimension	Dimensiones	diameter 72	mm ØD
			length 163	mm L (MOL)
			weight 70	g
			universal	
Brennstellung	Burning position	Posición de funcionamiento	10	µF/50Hz
Kondensator	Capacitor	Condensador	required	
Vorschaltgerät	Control gear	Balasto	not required	
Zündgerät	Ignitor	Ignitor	20	Quantity
Stück/VE	Piece/box	Piezas/caja	na	ANSI
ANSI-Nr.	ANSI-No.	No.-ANSI	60662	IEC
IEC Norm	IEC Norm	IEC Norma	73/23/EEC	CE-EC
EG Konformität	EG Conformity	CE Conformidad	60662	DIN EN
			132008	VDE Reg.-Nr.
VDE Zertifikat	VDE Certificat	VDE Certificado	45013-KRQ	ISO 9001
Qualitäts System	Quality system	Sistema de calidad	Internal Ignitor	
Anmerkungen	Remarks	Notas		

Information in our Catalogue, Data sheet and Price list are subject to technical and formal changes without prior notice. Operating values and dimensions are valid with the usual slight deviations