



## SVLT 100 Long Life

### Natriumdampf-Hochdrucklampe

### High pressure sodium vapor lamp

### Lámpara de vapor de sodio en alta presión

Lampentyp	Lamp type	Tipo de lámpara	SVLT 100 LL	ASTRALUX
Artikel-Nr.	Part-No.	No.-Parte	A147-101850	Ordering code
Leistung	Power	Potencia	100	W
Spannung	Arc voltage	Tensión	100	V
Strom	Current	Corriente	1,2	A
Lichtstrom	Luminous flux	Flujo luminoso	9000	lm
Lichtausbeute	Luminous efficacy	Eficiencia luminosa	90	lm/W
Farbtemperatur	Colour temperatur	Temperatura de color	2050	°K (CCT)
Optisches Zentrum	Light center	Centro óptico	132+-5	mm (LCL)
Farbwiedergabe	Color rendering	Nivel de reproducción cromática	20	Ra (CRI)
			4	DIN 5035
Lebensdauer	Rated life	Duración/vida útil	33000	Hrs.
Glaskörper	Bulb	Ampolla/bulbo	tubular	
Typ	Type	Tipo	hard	
Ausführung	Finish	Acabo	clear	
Sockel	Cap/base	Casquillo/base	E40	
Abmessungen	Dimension	Dimensiones	diameter 46	mm ØD
			length 211	mm L (MOL)
			weight 170	g
Brennstellung	Burning position	Posición de funcionamiento	universal	
Kondensator	Capacitor	Condensador	12	µF/50Hz
Vorschaltgerät	Control gear	Balasto	required	
Zündgerät	Ignitor	Ignitor	required	
Stück/VE	Piece/box	Piezas/caja	49	Quantity
ANSI-Nr.	ANSI-No.	No.-ANSI	60662	ANSI
IEC Norm	IEC Norm	IEC Norma	73/23/EEC	IEC
EG Konformität	EG Conformity	CE Conformidad	60662	CE-EC
			132008	DIN EN
VDE Zertifikat	VDE Certificat	VDE Certificado	45013-KRQ	VDE Reg.-Nr.
Qualitäts System	Quality system	Sistema de calidad	Long Life	ISO 9001
Anmerkungen	Remarks	Notas		

Information in our Catalogue, Data sheet and Price list are subject to technical and formal changes without prior notice. Operating values and dimensions are valid with the usual slight deviations